



Model TS-10 and TS-11

Vandal-Resistant Push Buttons

Specifications

- Momentary action switch
- DPDT contacts rated 4A at 25 VDC or 120 VAC
- Red and green LEDs operate on 12 or 24 VDC, independently wired
- Switch depth behind plate: 1-1/2"
- Switch is constructed to meet IP65 standard for direct water spray
- UL listed and CSA certified components
- UL 294 listed

Features

- Switch mounted on single gang wall plate or 1-3/4" narrow wall plate
- Labeled "PUSH TO EXIT"
- Switch terminated with colored leads

Options

- 430 stainless steel wall plate
- Order TS-10-302 for weather-proof model
- Order TS-10 for single gang wall plate
- Order TS-11 for narrow wall plate

Models

TS-10

UL 3/4" Diameter Metal Push Button, DPDT 4A, Momentary Continuous Contacts, "PUSH TO EXIT", Red & Green LEDs, Single Gang Stainless Steel Plate

TS-11

UL 3/4" Diameter Metal Push Button, DPDT 4A, Momentary Continuous Contacts, "PUSH TO EXIT", Red & Green LEDs, 1-3/4" Stainless Steel Plate

ALARM CONTROLS



ASSA ABLOY

ASSA ABLOY, the global leader
in door opening solutions