

Electric Door Strike

SD-995C For metal doors, 12VDC

SD-995C24 For metal doors, 24VDC

The **SECO-LARM** Electric Door Strike can be used to convert cylindrical lock sets into an electronic access-controlled locking system. Combine with an optional digital keypad such as the **SECO-LARM® SK-1131-SPQ** for keyless high security.

Features:

- Field-programmable in just seconds for fail-safe or fail-secure applications
- Can be used with virtually any cylindrical door locking system
- Use with an optional digital keypad
- Suitable for office-type applications
- Symmetrical-sized, reversible for right-hand or left-hand doors
- Shallow design for use with most metal doors
- Powered by a solenoid, not a buzzer coil
- Jaw strength – 2,000 lbs
- Stainless-steel lip (keeper) for strength and long life
- Non-polarized connection; wires can be reversed
- Tested to 1 million cycles
- Includes trim plate to hide gaps in installation
- Optional lip-extension brackets available:
 - **SD-995C-LE25** – 1” Extension
 - **SD-995C-LE50** – 2” Extension



Also Available from SECO-LARM®:



SD-994C
SD-994C24
Electric Door Strike
for Wood Doors



SD-996C-NUQ
Universal Door Strike

Specifications:

Model	SD-995C	SD-995C24
Operating voltage	12VDC	24VDC
Current draw	250mA	150mA
Operating temperature	14°~113° F (-10°~45° C)	
Jaw strength	2,000-lb	
Dimensions	4 ⁷ / ₈ "x1 ¹ / ₄ "x1 ¹ / ₄ " (124x32x32 mm)	

SECO-LARM® U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606

Phone: (949) 261-2999 | (800) 662-0800 Fax: (949) 261-7326

Website: www.seco-larm.com Email: sales@seco-larm.com



Copyright 2014 © SECO-LARM U.S.A., Inc. All rights reserved.
All trademarks are the property of SECO-LARM U.S.A., Inc. or their respective owners.
The SECO-LARM policy is one of continual development. For that reason, SECO-LARM reserves the right to change prices and specifications without notice. SECO-LARM is not responsible for misprints.

SECO-LARM® ENFORCER® CRIMEBUSTER® CBA SLI®

PiSD-995C_141015.docx