

FPM-1000-ENC Enclosure with Dead Front Door

www.boschsecurity.com



BOSCH
Invented for life



- ▶ Key-locked front door with clear viewing panel, easily unhinged for installation
- ▶ Dead front door covering the electronics and batteries, easily opened or removed
- ▶ Three-point mounting for stability, semi-flush or surface mounting
- ▶ Three triple knockouts (½ in., ¾ in. and 1 in.) for easy cabling
- ▶ Room for two backup batteries (7 Ah or 18 Ah)

The FPM-1000-ENC is a red, UL listed fire enclosure with a dead front door for use with the FPA-1000 Analog Addressable Fire Panels. The hinged, key-locked front door has a clear viewing window. The dead front door installs inside the hinged front door and covers the electronics and batteries. It is easy to open or remove for access.

- Mount to a minimum of 3/8-inch plasterboard (Drywall) with stud spacing less than 24 inches on center
- Wall anchors must be used that support at least 110 lbs (50 kg)

Certifications and approvals

Region	Certification	
USA	CSFM	see our website
	FDNY-CoA	#6101

Installation/configuration notes

Mounting Considerations

- Ensure that the environmental conditions of the mounting location comply with the technical specifications
- Ensure that there is sufficient room to open the cabinet door and dead front door fully, and to easily install, wire, and maintain the panel

Parts included

Quant.	Component
1	Enclosure base and door
1	Dead front door
1	Lock and key (#1358)
1	Hardware pack
1	Literature pack <ul style="list-style-type: none"> • Wiring diagram • Installation instructions

Technical specifications

Environmental

Environment:	Indoor, dry
Protection class (IEC 60529):	IP 30
Relative humidity:	Up to 95%, non-condensing
Temperature (operating):	+32°F to +120°F (0°C to +49°C)
Temperature (storage):	+14°F to +131°F (-10°C to +55°C)

Mechanical

Cable entries:	Triple knockouts (½ in., ¾ in. and 1 in.)
Color:	Red

Dimensions

• enclosure (W x H x D):	14.5 in. x 4.3 in. x 22.7 in. (36.8 cm x 10.9 cm x 57.7 cm)
• with trim ring (W x D):	17.5 in. x 25.6 in. (44.5 cm x 65.0 cm)
• semi-flush mounted (H recessed):	3.25 in. (8.25 cm)
• semi-flush mounted (H flush):	1.05 in. (2.7 cm)
Material:	Cold rolled steel, 19 gauge (1.2 mm)
Mounting holes:	3, on back

Weight

• enclosure:	18.3 lb (8.32 kg)
• gross weight (including packaging and manuals):	24.5 lb (11.1 kg)

Ordering information

FPM-1000-ENC Enclosure with Dead Front Door

Enclosure with dead front door

Order number **FPM-1000-ENC**

Accessories

FPM-1000-SFMK Semi-flush Mounting Kit

The FPM-1000-SFMK Semi-flush Mounting Kit includes a trim ring and 4 screw covers.

Order number **FPM-1000-SFMK**

D102 Replacement Key

Replacement key (#1358) for LOCK-1358 and the D101 lock.

Order number **D102**

Represented by:

Americas:

Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security
Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd.
201 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

America Latina:

Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
latam.boschsecurity@bosch.com
www.boschsecurity.com