

PTZ controller with Integrated 3-Axis Joystick



- Controls up to 255 cameras
- Multiple protocol supported in each channel
- RS-485 / RS-422 communication (TX: 3, RX: 1)
- Programmable user preferences (Preset, Tour, Pattern, etc.)
- Built-in 3-axis proportional joystick
- Built-in 2-line LCD
- User password support
- Operate with 9V battery
- DVR interface
- USB mouse function

Technical Specification

Model	KTX-1200
Communication	Interface: RS-482 / 422
	Operating distance: 4000ft (1.2km) on 24 AWG wire
	Protocol: Multiple (Pelco-D, Pelco-P, Wonwoo, etc.) (Baudrate selectable)
Connector Type	Terminal block (8p)
Keyboard Button	Rubber buttons
	Numeric keypad and camera function keys
Power	DC 12V or 9V battery (Battery mode) Max. 140mA
LCD Display	Graphic display 16 character / 2 lines
Operating Temperature	0 °C ~ 45 °C (32 °F ~ 113 °F)
Humidity	10% ~ 70% Non-condensing
Dimension	280(W) x 100.08(H) x 179.53(D) mm
Weight	Net: 0.7 kg / Gross: 1.7 kg
Package include	KTX-1200 keyboard, Adapters, USB cable, Manual, Terminal block (8p)