

# AVK-P1000

PTZ CONTROLLER

Accessories



FUNCTION

- Vector variable speed joystick
- Communication between camera and keyboard, one point to multi half-duplex
- Communication: RS485
- Communication Protocol: Pelco-D/P



DIMENSION

• Unit : mm (Inch)



SPECIFICATION

DESCRIPTION	
PRODUCT	VECTOR KEYBOARD
POWER SUPPLY	DC12V+10%/50HZ 500MA
OPERATING TEMPERATURE	-20°C ~ +55°C
OPERATING HUMIDITY	≤90% NON CONDENSING
COMMUNICATION	RS-485
INTERFACE	4PIN LINE PRESSING TERMINALS
BAUD RATE	1200BPS, 2400BPS, 4800BPS, 9600BPS, 19200BPS
COMMUNICATION PROTOCOL	PELCO-D, PELCO-P
COMMUNICATION BETWEEN CAMERA AND KEYBOARD	ONE POINT TO MULTI-POINTS HALF-DUPLEX
JOYSTICK	VECTOR VARIABLE SPEED JOYSTICK
DISPLAY	LCD
COMMUNICATION DISTANCE	1.2KM
CONTROL CAMERA QUANTITY	128
OSD MENU	ENGLISH
DIMENSION	220x130x10(mm)