



**ULT-P2BXIRM4794** 2 Megapixel IP Outdoor Bullet, 4.7-94mm Motorized Lens, 360' EXIR Range, PoE/12VDC, SD Card Slot

2 Megapixel Plug & Play	4.7-94mm Motorized Zoom	H.264 / H.264+
True Day/Night	True WDR	EXIR 360' IR Range
Audio In/Out	IP67 Weatherproof	PoE/DC12V
ONVIF	SD Card Slot	Free App iOS & Android
FREE CMS	FREE CMS	Free MAC Client

Features

- 2 Megapixel (1920x1080) Resolution
- 4.7-94mm Motorized Varifocal Lens
- H.264/H.264+, MJPEG Compression
- True Day/Night
- True WDR 120dB
- 360' EXIR Range
- Audio Input/Output
- IP67 Weather Resistant
- 12VDC/PoE Operation
- ONVIF
- SD Local Storage, 128GB
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free MAC client

Mounting Options



Ordering Information

**ULT-P2BXIRM4794:** 2 Megapixel Motorized Bullet, 4.7-94mm

Model Number	ULT-P2BXIRM4794
Image Sensor	1/2.8" progressive scan CMOS
Min. illumination	0.005 Lux @ (F1.4, AGC ON), 0 Lux with IR
Shutter time	1s ~ 1/100.000s
Lens	4.7 - 94 mm @ F1.4 Motorized VF lens
Day & night	IR cut filter with auto switch
Digital noise reduction	3D DNR
Wide dynamic range	True WDR
Backlight compensation	Yes, zone configurable
Video compression	H.264 / H.264+ / MJPEG / MPEG4
H.264 compression profile	Main profile
Bit rate	32 Kbps ~ 16 Mbps
Dual stream	Yes
Max. image resolution	1920 x 1080
Frame rate	60Hz: 60fps (1920 x 1080), 60fps (1280 x 720)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
On board Storage	Built-in Micro SD/SDHC/SDXC card slot, up to 128 GB
Audio	1/1
Alarm	1/1
Alarm trigger	Motion detection, tampering alarm
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
System compatibility	ONVIF, PSIA, CGI
General functionalities	User authentication, watermark
Communication interface	1 RJ45 10M/ 100 M Ethernet interface
Operating conditions	-30°C ~ 60°C (-22°F ~ 140°F) humidity 90% or less (non-condensing)
Power supply	12 VDC ± 10%, PoE (802.3at)
Power consumption	Max. 18W
Ingress protection	IP67
EXIR range	up to 360ft
Dimensions	3.93"x4.09"x12.28" (100x103.9x311.8mm)
Weight	4.41 lbs (2000g)
Included Accessories	IUM-BRJB1 Junction Box #1

\*To use these mounts with the selected cameras drill the holes needed into the mount using the diagram included with the camera. InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.