



## VR237FS Flush Mount Video Door Station



Front View

### Features

- Simple, push button Call operation
- Hands-free reply
- Modern styling
- Clear voice quality
- LEDs for dark entryways
- IP55 Rated for outdoor use
- Lighted pushbutton and nameholder
- Rugged metallic finish (2.5mm thick faceplate)

### Required Components

**NOTE:** The VR237FS Flush Door stations must be used with the VK237 series video-intercom systems and indoor master stations. A maximum of two (2) VR237FS stations can be installed on each system. They are also fully compatible with the (model# DL237) DoorLINQ™ smartphone adapter.

### VR237FS Flush Mount Video Door Station

The VR237FS Flush Door stations from Alpha Communications® are used with the VK237 series video-intercom systems, when one (or two) flush mount door entry stations are required. The unit provides natural, clear voice communication, simple push button call operation, and hands free reply, with a built-in wide-angle HD color camera. The station is ideal for outdoor use, in home, office, plant, warehouse, retail applications, and is IP55 rated for outdoor use.

The operation of the station is simple and efficient. The caller, by pressing the "CALL" button, causes an audible/visual signal at the inside video-intercom location(s). The resident can visually see who is at the door, speak to the visitor hands-free and if required, operate an optional electric door strike from the built-in relay.

The VR237FS is fully compatible with the model# DL237 DoorLINQ™ smart phone/smart tablet adapter.

### Specifications

<b>Dimensions:</b>	<b>O.D.</b> Height: 7.88" (201mm) Width: 5.12" (131mm) Depth: 0.25" (7mm)
	<b>I.D.</b> Height: 6.70" (171mm) Width: 4.35" (111mm) Depth: 1.58" (41mm)
<b>Finish:</b>	Brushed anodized aluminum (2.5mm thick faceplate) with built-in nameholder
<b>Controls:</b>	Single push button with self-wiping contacts and built-in Blue L.E.D. indicator
<b>Camera:</b>	HD color camera built-in with 104 degree angle of view with adjustable gimbal
<b>Connections:</b>	Pigtail wire connectors
<b>Housing:</b>	Flush back box / housing included

### Architects' And Engineers' Specifications

Flush Door Entry Video Door Station(s) shall be Alpha Communications® VR237FS with momentary action push button for "CALL" operation. The unit(s) shall be constructed of 2.5mm thick aluminum faceplate with an IP55 rating for resistance to weather. The unit(s) shall feature a built-in HD (104 degree) wide-angle color camera, illuminated call button and illuminated nameholder, speaker/microphone and door release relay. A flush backbox/housing shall be included.

Pigtail wiring harness shall be provided for electrical connections.

Contractor shall observe all national, and local electrical and building codes.

42 Central Drive • Farmingdale • NY • 11735-1202 • Phone: (631) 777-5500 • Fax: (631) 777-5599  
 TOLL-FREE: (800) 666-4800 • Web: AlphaCommunications.com • Email: info@alphacommunications.com

Copyright© 1998-2017 Alpha Communications® - All Rights Reserved.  
 Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.