



## AEMOD8 Voice / Data External Modem (AlphaEntry™ series)



### Architects' And Engineers' Specifications

The External Voice/Data Modem(s) shall be Alpha Communications® AlphaEntry™ AEMOD8 or equivalent.

The AEMOD8 shall be used in conjunction with the AlphaEntry™ PC master station and shall be plugged into a USB 2.0 connector on the PC master station.

The AEMOD8 shall be bus powered and shall have an extender cable for easy installation. The AEMOD8 shall have an RJ11 jack for the connection of the system telephone / telephone line.

Contractor shall observe all local and national electrical and building codes.

### AEMOD8 External Voice/Data Modem



The Alpha Communications® AEMOD8 AlphaEntry™ External Voice/Data Modems are designed to be used with a variety of AlphaEntry™ PC master stations when the internal or other modem is not fully compatible with all of the voice and data requirements of the AlphaEntry™ software. If the internal or other supplied modem is compatible with the AlphaEntry™ hardware and software, the AEMOD8 may not be required.

The AEMOD8 provides a simple and easy way to connect an analog telephone line to the AlphaEntry™ master station, using a plug-in Universal Serial Bus (USB) interface. The AEMOD8 is powered by the USB port and requires no additional external power.

### Features

- Connects externally to a USB 2.0 port with provided extender cable
- Speed: Data up to 56kbps
- V.92 software support
- Supports caller ID, wake on ring, telephone answering (V.253), modem on hold
- Has RJ11 jack for telephone / telephone line
- Small, compact footprint
- USB Powered

### Specifications

<b>Dimensions:</b>	1.00"w (26mm) x 0.75"h (20mm) x 2.625"d (67) less USB cable
<b>Weight:</b>	.35 lbs. Boxed