



ULT-P6PAN

6 Megapixel Outdoor Vandal IP Plug & Play Panoramic Camera, 1.27mm Lens, PoE/DC 12V, SD Card Slot, Audio

Features

- 6 Megapixel (3072x2048) Max Resolution
- Fixed Lens
- Up to 5 Channel Support: 360 Fisheye/Panoramic/ePTZ
- 1.27mm Fish Eye Lens
- H.264/MJPEG
- True Day/Night
- 30' EXIR Range
- Audio Input/Output
- Built-in Mic
- IP66 Weather Resistant
- IK10 Vandal Resistant
- 12VDC/PoE Operation
- ONVIF
- SD/SDXC Card slot up to 64 GB
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free Mac Client

| | |
|-------------------------|--|
| Image Sensor | 1/1.8" progressive scan CMOS |
| Min. illumination | 0.05 lux @ (F1.2, AGC ON), 0.3 lux @ (F2.8, AGC ON), 0 lux with IR |
| Shutter Speed | 1/25 (1/30)s ~ 1/100,000s |
| Lens | 1.27mm @F2.8, angle of view: 360° |
| Lens mount | M12 |
| Day & Night | True Day/Night with ICR |
| Video Compression | H.264/MJPEG |
| H.264 Type | Baseline Profile / Main Profile / High Profile |
| Video Bit Rate | 32 Kbps – 16 Mbps |
| Max. Resolution | 3072 x 2048 |
| Frame Rate | High-frame Mode: support 60Hz: 1 x fisheye (3072 x 2048, 25fps) or (2048 x 2048, 30fps) or 4 x PTZ at (1024 x 768, 30fps) Multi-channel Mode: support (1024 x 768, 12.5fps) 60Hz: 1 x fisheye (1280 x 1280, 15fps) and 1 x panoramic (2048 x 1536, 15fps) and 3 x PTZ (1024 x 768, 15fps) |
| Number of Streams | High Frame Rate Mode: 1 or 4 Multi-Channel: up to 5 (No sub-streams) |
| Digital Noise Reduction | 3D DNR |
| Wide Dynamic Range | Digital WDR |
| Image Setting | Saturation, Brightness, Contrast, Hue, Sharpness, AGC, White Balance |
| High Light Compensation | Support |
| Day/night Switch | Auto / Manual / Scheduled / Alarm trigger |
| Network Storage | NAS |
| Alarm trigger | Motion detection, dynamic analysis, tamper alarm, network disconnect, IP address conflict, storage full, storage error |
| Protocols | TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour |
| Security | User Authentication, Watermark, IP address filtering, Anonymous access |
| Standard | ONVIF, PSIA, CGI |
| Communication Interface | 1 RJ45 10M/100M/1000M Ethernet port 1 RS-485 interface (-S) |
| On-board storage | Built-in Micro SD/SDXC slot, up to 64 GB |
| Operating Conditions | -30 °C – 60 °C (-22 °F – 140 °F) Humidity 95% or less (non-condensing) |
| Power Supply | PoE /DC 12V±10% |
| Power Consumption | Max. 11W |
| IR range | Max. 30ft |
| Audio | In/Out, Built-in Mic |
| Environmental | IP66 Weather Resistant |
| Protection | IK10 |
| Dimensions | 164 x 152.8 x 43.8mm (6.46" x 6.02" x 1.72") |
| Weight | 3.08 lb |

Ordering Information

ULT-P6PAN: 6 Megapixel Panoramic Camera