

WIRELESS BACKUP CAMERA SYSTEM WITH MIRROR MONITOR

RVS - 091407

REAR VIEW
SAFETY
A Safe Fleet Brand



The new Digital Wireless Backup Camera System will revolutionize the backup camera industry. The new digital wireless camera guarantees no interference up to 70ft so you get a great and beautiful picture at all times. The system is complete with a color 4.3" TFT-LCD Mirror Monitor with distance grid lines which can either attach to the existing rear view mirror or replace it. The camera boasts a 130° MTV136 High Definition camera with 9 infra-red night vision lights which enables you to see in total darkness. The backup system comes with all the wires, connectors and mounts you will need. The camera is completely weatherproof with an IP68 rating, strong and reliable, shock resistant, with a 10G vibration rating (highest in the industry). It comes with a full year warranty.

WIRELESS BACKUP CAMERA SYSTEM WITH MIRROR MONITOR

**REAR VIEW
SAFETY**

A Safe Fleet Brand

RVS - 091407

- SUPER SHARP 4.3" TFT LCD DISPLAY MIRROR MONITOR
- COMPLETELY WEATHERPROOF WITH AN IP68 RATING
- 130° MTV136 HIGH DEFINITION CAMERA WITH 9 INFRA - RED NIGHT VISION
- SHOCK RESISTANT WITH A 10G VIBRATION RATING



MONITOR

TYPE	TFT LCD
SCREEN SIZE	4.3"
DOT RESOLUTION	1440 (H) X 234 (V)
DISPLAY FORMAT	16:9
DISPLAY BRIGHTNESS	350CD/m ²
VIEWING ANGLE	90°
VIDEO INPUT	1 CHANNEL
VIDEO SOURCE	1VP - P, 75 Ω
POWER SUPPLY	DC 12V - 24V (+/- 10%)
POWER CONSUMPTION	5W
OPERATING TEMPERATURE	-10 °C ~ +65 °C
VIDEO SYSTEM	AUTO NTSC / PAL
OVERALL DIMENSIONS	10" (L) X 3.5" (H) X 1" (D)
WEIGHT	400G
VIBRATION RATING	5G
SYNC AREA	154.08 (H) X 86.58 (V)
SYNC SYSTEM	INTERNAL

CAMERA

SENSOR	MT9V136
PICTURE ELEMENTS	250,000 PIXELS
GAMMA CORRECTION	R=0.45 TO 1.0
IMAGE SENSOR	480 TV LINES, PAL: 500 (H) X 582 (V) NTSC: 510 (H) X 492 (V)
LENS	2.1MM
VIEW ANGLE	130°
SYNC SYSTEM	INTERNAL SYNCHRONIZATION
INFRA - RED DISTANCE	30 FEET (9 INFRARED)
USABLE ILLUMINATION	0 LUX (IR ON)
POWER SOURCE	DC 12V-24V (+/- 10%)
S/N RATIO	MORE THAN 48DB
ELECTRONIC IRIS	1/50, 160-1/100,000SEC
VIDEO OUTPUT	1VP - P, 75 Ω
IR SWITCH CONTROL	ACDS AUTOMATIC CONTROL
VIBRATION AND IMPACT RATING	10G / 100G
OPERATING TEMPERATURE	-25°C ~ +50°C / RH 95% MAX
STORAGE TEMPERATURE	-25°C ~ +60°C / RH 95% MAX