

SimpleSight™ 130° Wireless Backup Camera with 18 Infra-Red Illuminators

RVS-55W

REAR VIEW SAFETY
A Safe Fleet Brand



Perfection takes time, especially with something as complicated as wireless transmission. Our newest wireless camera, part of our new SimpleSight™ Series was born from years of testing and multiple prototypes. This camera boasts a 100' digital wireless range which is guaranteed to work even at highway speeds. Users can pair this wireless camera with our compatible wireless monitor (**RVS-15WM**) without leaving the cab via Instant Pair technology.

Specifications

SENSOR	1099 COLOR CAMERA
EFFECTIVE PIXEL ARRAY	976 (H) X 496 (V)
PICTURE ELEMENTS	480,000 PIXELS
NTSC OUTPUT	720 (H) X 480 (V)
PAL OUTPUT	720 (H) X 576 (V)
OPTICAL FORMAT	1/4 INCH
CAMERA CORRECTION	R=0.45-1.0
LENS	F=2.5MM
WATERPROOF RATING	IP69K
POWER CONSUMPTION	ABOUT 3.5W (IR ON)
POWER INPUT	DC10-32V

OPERATING TEMP.	-30°C ~ +70°C RH 90% MAX
STORING TEMP.	-30°C ~ +80°C RH 90% MAX
FREQUENCY	2400-2500 MHZ
TRANSMISSION TYPE	DIGITAL WIRELESS
TRANSMISSION RANGE	100 FT
VIDEO SOURCE	1VP-P 75Ω
S/N RATIO	MORE THAN 48 DB
WHITE BALANCE	AUTO
IR CONTROL	AUTO