

## MegaVideo® Compact IP Megapixel Cameras

H.264 Single or Dual Sensor True Day/Night Indoor Box-Style Compact IP Cameras with WDR (Wide Dynamic Range) Models

### Camera Models

1.3 Megapixel	1080p	1080p WDR	3 Megapixel	3 Megapixel WDR	5 Megapixel	10 Megapixel
AV1115v1	AV2115v1	AV2116DNv1	AV3115v1	AV3116DNv1	AV5115v1	AV10115v1
AV1115DNv1	AV2115DNv1		AV3115DNv1	AV3236DN	AV5115DNv1	AV10115DNv1
AV1115DNAv1	AV2115DNAv1		AV3115DNAv1		AV5115DNAv1	AV10115DNAv1



MegaVideo® Compact multi-megapixel cameras provide ample resolution to zoom-in for details in live or recorded video. These box camera solutions are available at 1.2-, 1.3- 1080p, 3-, 5- or 10-megapixel resolutions with the fastest frame rates in the industry. MegaVideo® Compact cameras are “build to order” solutions: select the best lens, auto-iris, True Day/Night, Wide Dynamic Range (WDR), color-only and enclosures for specific applications (sold separately).

Customizable Lens and Housing Options

Dual Sensor (AV3236)

True Day/Night with IR Cut Filter

Pixel Binning Mode on 3, 5, and 10MP Models

Dual Mode: 1080p/10MP

Wide Dynamic Range Available on Some 1080p and 3MP Models

Casino Mode™ Maintains at Least 30fps on AV2115 Models

Dual Encoder H.264/MJPEG

### Features:

- Small Size for Flexible Mounting Options
- Many Lenses to Choose From
- 3MP WDR + 1.2MP B/W Dual Sensor Camera Offers Strong Performance in Low Light and High Contrast Lighting Conditions
- Optional True WDR up to 100dB at Full Resolution: See Clearly in Shaded and Bright Light Conditions Simultaneously on Dual Sensor and Some 1080p and 3MP Models
- Binning Mode for Strong Low Light Performance on 3MP, 5MP and 10MP Models
- Day/Night, Color-Only or Auto-Iris Options
- True Day/Night Functionality with Removable IR Cut Filter
- Use with Arecont Vision Housings, or as a Standalone Camera (Dual Sensor Model is Incompatible with D4 Series Housings)
- PoE and Auxiliary Power: 12–48V DC/24V AC (Auxiliary Power Not Available for Dual Sensor Model)
- Dual Encoder H.264/MJPEG
- Privacy Mask, Motion Detection, Flexible Cropping, Bit Rate Control, Multi-Streaming and Forensic Zooming
- Casino Mode™ in 1080p Models (Maintains 30fps or Higher)
- Reduced Overall System Cost

### Model Specific Features

Model	Resolution	Frame Rate	Features		
AV1115	1.3MP	42fps			
AV2115	1080p	31fps		Casino Mode™	
AV2116	1080p	31fps	WDR		
AV3115	3MP	21fps			Binning
AV3116	3MP	21fps	WDR		Binning
AV3236	3MP / 1.2MP	18fps / 40fps	WDR	Dual Sensor	Binning
AV5115	5MP	14fps			Binning
AV10115	10MP	7fps			Binning

### Build-to-Order Options

DN*	True Day/Night
AI*	Auto-Iris

\* Not Available for AV3236 Dual Sensor

Camera Imaging Specifications

Model	AV1115	AV2115	AV2116	AV3115	AV3116	AV3236	AV5115	AV10115	
Image Sensor (CMOS)	1.3MP*	1080p	1080p*	3MP*	3MP	3MP Color 1.2MP B/W	5MP	10MP	
Optical Format	1/2.7"	1/2.7"	1/3.2"	1/2.5"	1/3.2"	1/3.2" @ 3MP 1/3" @ 1.2MP	1/2.5"	1/2.3"	
Minimum Illumination	Color	0.1 Lux	0.1 Lux	0.3 Lux	0.3 Lux	0.3 Lux	0.2 Lux	0.3 Lux	0.42 Lux
	Color Binning	-	-	-	0.15 Lux	0.15 Lux	-	0.15 Lux	0.21 Lux
	True Day/Night (-DN Models)	0 Lux, IR sensitive	0 Lux, IR sensitive	0 Lux, IR sensitive	0 Lux, IR sensitive	0 Lux, IR sensitive	0 Lux, IR sensitive	0 Lux, IR sensitive	0 Lux, IR sensitive
Full FOV Resolution	1280 H x 1024 V	1920 H x 1080 V	1920 H x 1080 V	2048 H x 1536 V	2048 H x 1536 V	2048 H x 1536 V @ 3MP 1280 H x 1024 V @ 1.2MP	2592 H x 1944 V	3648 H x 2752 V	
1/4 Resolution	640 H x 512 V	960 H x 540 V	960 H x 540 V	1024 H x 768 V	1024 H x 768 V	1024 H x 768 V @ 3MP 640 H x 512 V @ 3MP	1296 H x 968 V	1824 H x 1376 V	
Dynamic Range	69dB	69dB	Up to 100dB	70.1dB	Up to 100dB	Up to 100dB	70.1dB	57.2dB	
Frame Rates	Full Resolution	42fps (1280x1024)	31fps (1920x1080)	31fps (1920x1080)	21fps (2048x1536)	21fps (2048x1536)	1.2MP 40fps (1280x960) 3MP 18fps (2048x1536)	14fps (2592x1944)	7fps (3648x2752)
	Binning Mode	-	-	-	46fps (1024x768)	21fps (1024x768)	-	34fps (1296x972)	30fps (1920x1080)
	Upscaled	-	-	-	-	-	1.2MP 18fps (2048x1536)	-	-
	Dual Stream	-	-	-	-	-	1.2MP 11fps @ 1280x960 3MP 2048x1536	-	-
	Dual Stream Upscaled	-	-	-	-	-	1.2MP 8fps @ 2048x1536 3MP 2048x1536	-	-

\* Effective

Data Transmission	Compression Type	H.264 (MPEG-4, Part 10)/Motion JPEG 21 levels of quality
	Network Protocols	RTSP, RTP/TCP, RTP/UDP, HTTP, DHCP, TFTP
	Network Interface	100Base-T Ethernet
	Multi-Streaming	8 Non-identical streams


Environmental	Operating temperature	-5°C (23°F) to +45°C (113°F)
	Humidity	0% to 90% (non-condensing)
	Stable image temperature	0°C (32°F) to +50°C (122°F)
	Storage temperature	-20°C (-4°F) to +60°C (140°F)

Programmability	Wide dynamic range switch control
	Binning Mode (AV3115, AV3116, AV5115, AV10115)
	Flexible cropping
	On-camera real-time motion detection and privacy mask with 1024 detection zones
	Backlight compensation
	Auto multi-matrix white balance
	50/60Hz selectable flicker control
	Electronic pan, tilt, zoom (PTZ)
	Electronic image flip: 180° rotation
	Resolution windowing down to 1x1 pixel for JPEG and 2x2 pixels for H.264
	Programmable shutter speed to help control motion blur
	Casino Mode™ in 1080p Models (Maintains 30fps or Higher)
	MoonLight™ Mode: extended exposure and noise cancellation
	Programmable resolution, brightness, saturation, gamma, sharpness, tint
	Simultaneous delivery of full field-of-view and zoomed images
	Bandwidth and storage savings by running at 1/4 resolution
Bit rate and bandwidth limitation control	

Mechanical	Casing	Die-cast aluminum chassis C/CS lens mount
	Total Unit Dimensions	Unit 3" W (76mm) x 1.25" D (31.7mm) x 2.5" H (63.5mm) (w/o lens)
		Packaged 4" W (102mm) x 4" L (102mm) x 3.7" H (94mm)
	Weight	Unit 5.8oz (164 grams) w/o lens
Packaged 0.7 lbs (0.318kg)		

Compliance	Industry Standard	ONVIF Profile S and PSIA Conformant
	Listings	UL (CB)
	FCC Compliance	47 CFR 15 Class A
	Environmental	RoHS, REACH, WEEE
	Markings	(CE) EN55022 Class A, EN55024, EN61000-3-2, EN61000-3-3, EN60950-1

Electrical	Input/Output	General purpose opto-coupled
	Power Over Ethernet	PoE 802.3af, Class 3
	Auxiliary Power	12-48V DC, 24V AC (AV3236 is PoE only)
	Power Consumption	4.5 Watts DC Power



# MegaVideo® Compact D4SO Series IP Megapixel Cameras

1.3–5MP H.264 All-in-One True Day/Night Indoor or Indoor/Outdoor Dome IP Cameras

Kit Part Number	Kit Components	Camera Part Number & Description	Lens Part Number & Description	Housing Part Number & Description
D4SO-AV1115DNv1-3312	AV1115DNv1 + MPL3312A Varifocal and D4SO Surface Mount Outdoor Dome	AV1115DNv1: 1.3 Megapixel, 42 fps, H.264/MJPEG Day/Night Camera, 1280x1024, motorized IR cut filter, Compact, 12VDC/24VAC/PoE	MPL3312A: Arecont 3.3-12mm, 1/2.5, f1.4 CS-mount, IR corrected and for use with both WDR and non-WDR cameras	D4SO: Outdoor Surface Mount Dome
D4SO-AV2115DNv1-3312	AV2115DNv1 + MPL3312A Varifocal and D4SO Surface Mount Outdoor Dome, Casino Mode	AV2115DNv1: 1080p, 31 fps, Megapixel H.264/MJPEG Day/Night Camera, 1920x1080, motorized IR cut filter, Compact, 12VDC/24VAC/PoE, Casino Mode	MPL3312A: Arecont 3.3-12mm, 1/2.5, f1.4 CS-mount, IR corrected and for use with both WDR and non-WDR cameras	D4SO: Outdoor Surface Mount Dome
D4SO-AV3115DNv1-3312	AV3115DNv1 + MPL3312A Varifocal and D4SO Surface Mount Outdoor Dome	AV3115DNv1: 3 Megapixel, 21 fps, H.264/MJPEG Day/Night Camera, 2048x1536, motorized IR cut filter, Compact, 12VDC/24VAC/PoE, Binning	MPL3312A: Arecont 3.3-12mm, 1/2.5, f1.4 CS-mount, IR corrected and for use with both WDR and non-WDR cameras	D4SO: Outdoor Surface Mount Dome
D4SO-AV5115DNv1-3312	AV5115DNv1 + MPL3312A Varifocal and D4SO Surface Mount Outdoor Dome	AV5115DNv1: 5 Megapixel, 14 fps, H.264/MJPEG Day/Night Camera, 2592x1944, motorized IR cut filter, Compact, 12VDC/24VAC/PoE, Binning	MPL3312A: Arecont 3.3-12mm, 1/2.5, f1.4 CS-mount, IR corrected and for use with both WDR and non-WDR cameras	D4SO: Outdoor Surface Mount Dome

**Accessories**

AV-CRMA	Corner Mount Adapter
AV-EBA	Light gray electrical box adapter
AV-JBA	Light gray junction box adapter (Fit 3/4" NPT Conduit)
AV-PMA	Pole Mount Adapter
AV-PMJB	Pendant Mount Bracket with Junction Box (Fits Cap 1.5" NPT, Box Fits 3/4" NPT)
AV-WMJB	Wall Mount Bracket with Junction Box (Fits Cap 1.5" NPT, Box Fits 3/4" NPT)
D4SO*	Outdoor 4" Dome
DOME5-1*	Recessed 5" Dome
HSG2	Outdoor PoE Housing compatible with HSG2-WMT Wall Mount
HSG2-WMT	Wall Mount for HSG2 Housing
MD-CAP	Wall Mount and Cap Accessory

\* Not compatible with Dual Sensor model

**Features:**

- Integrated Vari-Focal Lens (Accepts Additional Lenses)
- Casino Mode™ Guarantees Continuous 30fps Frame Rate Required by Gaming Industry Regulations (1080p Models)
- Binning Mode for Strong Low Light Performance on 3MP and 5MP Resolutions
- Day/Night and Color-Only Options
- Outdoor Rated IP66 and IK-10 Impact-Resistant Housing (D4SO)
- Easily Adjustable 2-Axis Gimbal
- PoE and Auxiliary Power: 12–48V DC/24V AC
- Dual Encoder H.264/MJPEG
- Privacy Mask, Motion Detection, Flexible Cropping, Bit Rate Control, Multi-Streaming and Forensic Zooming
- User-Friendly Webpage
- Reduced Overall System Cost
- Made in the USA

**All-in-One Solution**



**D4SO Mechanical**

<b>Casing</b>	Die-cast aluminum chassis	
	Polycarbonate Dome	
<b>Total Unit Dimensions</b>	Unit	Ø 5.5" (140.3mm) x 4.9" H (124.6mm)
	Packaged	8" W (203mm) x 7.5" L (190mm) x 6" H (152mm)
<b>Weight</b>	Unit	2.0 lbs (0.91kg) w/o camera    2.4 lbs (1.09kg) w/ camera
	Packaged	3.1 lbs (1.406kg)

