

HIKVISION

DS-2FP2020: External Security Microphone

General Information/Key Features

- Harmonization Code: 8525804000
- Country of Origin: US
- Reverse Polarity Protection
- Built-in lightning protection
- CE & FCC Compliant

Related Pages (Right click to open in new tab)

Shop Now. Visit the [DS-2FP2020](#) product page for detailed information

View [other Hikvision External Security Microphones](#)

View over 1300 [video surveillance products from Hikvision](#)

Scroll down to view the Hikvision DS-2FP2020 specification sheet



HIKVISION
DS-2FP2020

<https://www.surveillance-video.com> is a distributor/reseller of over 120,000 security products from over 100 brands.

For over 45 years, we have earned the confidence of our customers by providing professional service and support.

If you need technical support or assistance to install your security system or any other products purchased from Surveillance-video.com, you can call us @ **800-955-5201** at any time.

DS-2FP2020

Security Microphone

HIKVISION[®]
First Choice for Security Professionals

- High Sensitivity microphone, Omnidirectional Pickup, Clear Voice, Strong Anti-jamming capability
- Built-in lightning protection, reverse polarity protection
- RoHS Compliant
- CE & FCC Compliant



Specification

Model	DS-2FP2020
Spec	
Pickup Range	70m2
Transmission Distance	3000 Meters
Sensitivity	-34dB
Frequency Response	20Hz~20KHz
Type	Omnidirectional
SNR	60dB(1Mi 40 db Sound Src SPL) 40dB(10Mi 40 dB Sound Src SPL)1KHz at 1 Pa
Dynamic Range	70dB(1KHz at Max dB SPL)
Maximum Sound Pressure	100dB SPL (1KHz, THD 1%)
Output Impedance	600 Ohm Unbalanced
Output Amplitude	2.5Vpp/-25dB
Mic Type	Omnidirectional Microphone
Signal Processing	ANC Ambient Noise Cancellation Technology
Protection	30KV Air contact ESD、Lightning Protection, Reverse Polarity Protection

Driver Capability	Built-in pre-amp can directly drive headphones
Connection	3 Leads (Power, Audio, Ground)
Cable Type	3 Conductor Shielded Cable 0.5mm RVVP
Voltage	DC12V Power Supply
Current	25mA
Working Temperature	-25°C~70°C
Color	White / Dark Blue
Material	PVC
Dimensions	Φ 78mm × 28mm
Weight	82 Grams
Standards	European CE, US FCC and ISO9000