



## ELEV-P5PIR

5 Megapixel IP Plug & Play, Indoor Covert PIR Housing, Fixed Lens, WDR, Audio Input/Output, Built-in Mic, 12VDC, PoE

### Features

- 5 Megapixel Resolution
- Fixed Lens
- H.264/H.264+/H.265/H.265+
- 15 FPS Recording and Live
- D-WDR
- Smart Analytics
- Audio Input: Built-in Mic
- Audio Output
- PIR Detection
- Indoor Only
- 12VDC
- ONVIF
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS)
- Free MAC Client

Camera	ELEV-P5PIR
Sensor+DSP	SC5332 + SSC327DE
Image Sensor	1/2.7" Progressive scan CMOS Sensor
Min. Illumination	0.01lux(Color), 0lux(IR on)
Lens Mount	M12
Lens	3.7 mm@F2.5: horizontal FOV: 75°, vertical FOV:56°
IR	Not support
PIR Range	10m
Smart IR	Not support
Shutter Time	Auto/Manual, 1/3~1/10000s
Day/Night	IR cut filter with auto switch
Wide Dynamic Range	DWDR
Digital noise reduction	2D/3D DNR
Compression Standard	
Video Compression	H.264/H.264+/H.265/H.265+
H.264 Codec profile	Base/Main/High profile
H.265 Codec profile	Main profile
Video Bit Rate	11 Kbps~9 Mbps
Dual Streams	Support
Audio Compression	G.711A/G.711U
Audio Bit Rate	64 Kbps
Image	
Max. Image Resolution	5MP(2592 × 1944)
Frame Rate	50Hz: 15fps 5MP(2592 × 1944), 25fps 4MP(2560 × 1440), 25fps 3MP(2048 × 1536), 25fps 1080P(1920 × 1080), 25fps 960P(1280 × 960), 60Hz: 15fps 5MP(2592 × 1944), 28fps 4MP(2560 × 1440), 30fps 3MP(2048 × 1536), 30fps 1080P(1920 × 1080)
Sub Stream	50Hz:25fps D1(704 × 576),25fps CIF(352 × 288) 60Hz:30fps D1(704 × 480),30fps CIF(352 × 240)
Image Setting	Brightness/Contrast/Saturation/Hue/Sharpness
BLC	Support
HLC	Support
ROI	Support
Defog	Support
Network	
Network Storage	NAS(NFS/CIFS)
Protocols	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP, RTCP,NTP,IGMP,UPnP,SMT,UPnP-TM,P2P,Bonjour
Event	Motion Detection, Video Shelter
Smart Functions	Human Detection
System compatibility	Onvif 2.6,Profile S, CGI
Security	User authentication,IP address filtering,Video mask
Mobile Surveillance	iPhone, iPad,Android devices
Interface	
Communication interface	1 RJ45 10M / 100M Ethernet Port
Audio I/O	1/1
General	
Operating Conditions	-22°F ~ 140°F (-30°C ~ 60°C) Humidity 95% or less (non-condensing)
Power Supply	DC12V ± 10%
POE Supply	PoE (802.3af)
Power Consumption	MAX. 6W
Weather Proof	Indoor used only
Dimensions (W x H x D)	2.7 x 3 x 4.7 in (70 x 77 x120mm)
Weight	.6 lbs (280g)

### Ordering Information

**ELEV-P5PIR:** 5 Megapixel PIR Camera, 3.7mm