

FTV160/FRV160, FTV320/FRV320 Fiber Transmitter and Receiver

16- OR 32-CHANNEL DIGITALLY ENCODED VIDEO

Product Features

- 10-Bit Digitally Encoded Video for High-Quality Multichannel Video Transmission over a Single Fiber
- Single-Mode Fiber Support for Distances up to 54 km (33.6 mi)
- Exceeds All Requirements for EIA RS-250C Short-Haul Transmission Specifications
- Compatible with NTSC, PAL, or SECAM Video Standards
- Designed to Meet NEMA TS 1/TS 2 and Caltrans Traffic Signal Control Equipment Environmental Standards
- Laser Diode for Transmission of Optical Signals
- Voltage Transient Protection on All Power and Signal Input/Output Lines
- LED Status Indicators for Monitoring All Critical Operating Parameters
- Rack-Mountable Modular Design



FTV160S1ST

The **FTV160/FRV160** and **FTV320/FRV320** fiber transmitter and receiver transmit 16 or 32 channels of video, respectively, over one optical fiber. All models support single-mode fiber distances up to 54 km (33.6 mi).

The **FTV160/FRV160** and **FTV320/FRV320** plug-and-play design ensures ease of installation by requiring no electrical or optical adjustments. All models are shipped rack-mounted in the EURACK/USRACK chassis.

TECHNICAL SPECIFICATIONS

MODELS

Transmitter	Compatible Receiver	Fiber Optical Connector Type	Number of Fibers	Wavelength	Optical Power Budget	Maximum Transmission Distance*
Single Mode (9/125 µm)						
FTV160S1ST	FRV160S1ST	ST	1	1310 nm	18 dB	54 km (33.6 mi)
FTV160S1FC	FRV160S1FC	FC	1	1310 nm	18 dB	54 km (33.6 mi)
FTV320S1ST	FRV320S1ST	ST	1	1310 nm	18 dB	54 km (33.6 mi)
FTV320S1FC	FRV320S1FC	FC	1	1310 nm	18 dB	54 km (33.6 mi)
Note: This product requires a fiber installation with a minimum 30 dB connector return loss.						
*Distance may be limited by optical dispersion.						

VIDEO

Number of Channels	16 or 32
Video Input/Video Output	1.0 Vp-p, 75 ohms; NTSC, PAL, SECAM
Overload	>1.5 Vp-p
Bandwidth	10 to 6.5 MHz per channel
Differential Gain	<2%
Differential Phase	<0.7°
Tilt	<1%
Signal-to-Noise Ratio	67 dB at maximum optical loss budget
Max. Coaxial Cable (RG59)	100 m (300 ft) camera to fiber optic module to maintain 6 Mhz bandwidth

ELECTRICAL

MTBF	>100,000 hours
Input Power	
FTV/FRV160	90 to 264 VAC at 10 W maximum
FTV/FRV320	90 to 264 VAC at 20 W maximum
Rack Power Supply Output	9 VDC at 6.5 A
Fusing	1.25 A slow blow (rack power supply; plug-in modules are individually electronically fused)
Current Protection	Automatic resettable solid-state current limiters
Circuit Board	Meets IPC standards
LED Indicators	Video, Link, Power

MECHANICAL

Connectors	
Optical	ST or FC
Power	Terminal block
Video	BNC (gold-plated center pin)

GENERAL

Dimensions	48 × 19 × 15 cm (19" D × 7.5" W × 6" H)
Operating Temperature	-40° to 75°C (-40° to 167°F)
Storage Temperature	-40° to 85°C (-40° to 185°F)
Relative Humidity	0 to 95%, noncondensing
Unit Weight	
FTV160/FRV160	4.0 kg (8.8 lb)
FTV320/FRV320	5.3 kg (11.7 lb)
Shipping Weight	
FTV160/FRV160	5.08 kg (11.2 lb)
FTV320/FRV320	6.40 kg (14.1 lb)

CERTIFICATIONS/RATINGS†

- CE, Class A
- FCC, Class A
- UL/cUL Listed
- C-Tick
- Designed to meet NEMA TS 1/TS 2 and Caltrans traffic signal control equipment environmental standards

† At the time of this printing, all certifications are pending. Please consult the factory, our Web site (www.pelco.com), or the most recent B.O.S.S.® update for the current status of certifications.

RECOMMENDED MOUNTS

EURACK	4 RU rack accessory with European power supply
USRACK	4 RU rack accessory with North American power supply

Pelco by Schneider Electric

3500 Pelco Way, Clovis, California 93612-5699 United States

USA & Canada Tel (800) 289-9100 Fax (800) 289-9150

International Tel +1 (559) 292-1981 Fax +1 (559) 348-1120

www.pelco.com

Pelco, the Pelco logo, and other trademarks associated with Pelco products referred to in this publication are trademarks of Pelco, Inc. or its affiliates. All other product names and services are the property of their respective companies. Product specifications and availability are subject to change without notice.

©Copyright 2012, Pelco, Inc. All rights reserved.