

**DESCRIPTION:**

The IS-IPMV is an IP addressable video master station with a 3.5" color LCD monitor. It can be wall or desk mounted (desk stand included). The IS-IPMV offers handset (duplex) and hands-free (VOX/PTT) communication and can page up to 5 zones simultaneously. The unit is equipped with a door release button for the user to allow entry for the visitor. The IS-IPMV is also equipped with PTZ and brightness controls, giving the user control for camera angle and lighting to better see the visitor requesting entry. Six programmable speed dial buttons are also included for easy access to frequently called subs and paging zones. The IS-IPMV connects directly to a network using CAT-5e/6 cable and can communicate with any other IS station on its network. The station utilizes 802.3af compliant PoE or an external 24V DC supply, PS-2420UL.


IS-IPMV FEATURES:

- 3.5" LCD color monitor
- Handset for privacy or hands-free VOX / PTT communication
- Door release button
- Audio Output
- PTZ & brightness control
- 6 programmable speed dial buttons for calling stations or accessing paging zones
- Wall or desk mount (stand included)
- Connects using CAT-5e/6 cable
- 802.3af PoE compliant

IS-IPMV

IP Master Station

FEATURE CALL-OUT:



FEATURE CALL-OUT DEFINITIONS:

- [1] Handset
- [2] Speaker
- [3] Color LCD Monitor
- [4] Status LED (red)
- [5] Directory cards and covers
- [6] Speed dial buttons (6)
- [7] Microphone
- [8] OFF button
- [9] ADJUST button
- [10] PAN & TILT control button
- [11] ZOOM/WIDE button
- [12] Door release button
- [13] Transmit LED (red)
- [14] TALK button
- [15] MONITOR button
- [16] Dial keys
- [17] SETTING button
- [18] LIST button
- [19] PRIVACY button and LED (red)
- [20] TRANSFER button and LED (red)

SPECIFICATIONS:

Power Source:	24V DC or 802.3af PoE
Bandwidth:	320k ~ 8Mbps
Communication:	
Handset	Simultaneous Communication
Hands-free	Auto-voice actuation or PTT
Monitor:	3.5 inch color LCD
Paging capacity:	Simultaneous to max. 5 zones and/or stations
Mounting:	Desktop w/ stand or wall mount
Temperature:	32-104°F (0-40°C)
Dimensions:	7-1/2" H x 9-7/8" W x 2-3/8" D
Weight:	Approx. 1.81 lbs (820g)