



INNOVATIVE
HIGH DEFINITION SURVEILLANCE



OMNI
EZ HD TVI

 **KEZ-b1BR_IR**

720p HD Over Regular Coax or UTP
Outdoor IR Bullet, True Day/Night, 3-Axis
66' IR Range, 12VDC, IP66, -40°

KEZ-b1BR3IR: 2.8mm | KEZ-b1BR4IR: 3.6mm



OMNI EZ HD TVI

KEZ-b1BR_IR

Outdoor IR Bullet, True Day/Night, 3-Axis
66' IR Range, 12VDC, IP66, -40°


Features

- HD resolution of 720p30 for amazing image quality and useful digital zoom
- Twice the detail (pixels) compared with 960H/WD1 analog, and 2.7X the detail of traditional analog
- Operation over 'almost any' wire
 - Over 1000 feet on standard RG59 coax; longer distances on RG6
 - Up to 500' on one pair from a Cat5e cable (using optional KA-HDBAL1 balun pair).
- 1/3" progressive scan CMOS sensor with .01 lux native light sensitivity
- True Day/Night zero light operating range of 66 feet[†] or more from 24 IR LEDs
- Smart IR automatic exposure level adjust to deliver properly exposed images despite reflections and bright spots
- Digital Noise Reduction for low light image clarity and conservation of HDD space
- Easy mounting using 3-Axis positioning for convenient wall or ceiling mounting
- Your choice of 3.6mm lens or optional 2.8mm lenses to capture the desired field of view
- 12VDC operation with low current draw
- IP66 weather resistant, vandal resistant construction
- Extreme operating temperature range of -40°F ~ 140°F
- Compact size for unobtrusive surveillance



Technical Specifications

Imaging Device	1/3" Progressive Scan CMOS
Video Format	720p30 HD-TVI
Picture Elements	1280 (H) x 720 (V)
Horizontal Resolution	More than 1,000 HTVL
Sensitivity	0 lux IR LED on; .01 lux @ F1.2 (AGC On)
Lens Type	Fixed focal length 3.6mm nominal; optional 2.8mm
Angle of view	76.9° (3.6mm); 99.7° (2.8mm)
IR LED	24 LEDs, 850nm
IR Range [†]	66'
Smart IR Exposure Adjust	Internally controlled; active when IR enabled
Day & Night	Auto True D/N with motorized ICR, controlled by photo sensor
S/N Ratio	Over 52dB (NR On)
Sync. Mode	Internal
Auto Gain Control	0~15
Electronic Shutter	Auto: 1/30 ~ 1/50,000 second
White Balance	AWB
Color Correction	Nominal Gamma 0.45
2D-DNR	On
Video Output Connector Type	BNC 75Ω
Power Source	12VDC
Power Consumption	12VDC: 333mA IR LED On
Operating Temperature	-40 °F ~ 140 °F (-40 °C ~ 60 °C)
Environmental	IP66 weather resistant
Mechanical	Vandal resistant construction
Positioning	3-axis flexible positioning for wall or ceiling mounting Pan: 0~360° Tilt: 0~90° Rotate: 0~360°
Dimensions	Ø2.76" × 5.89" [Ø70 x 149.5mm]
Weight	.79 lbs./360 g
Certifications	CE / FCC / RoHS



KEZ-b1BR3IR: 2.8mm | KEZ-b1BR4IR: 3.6mm