

5 Megapixel Mini Dome Network Camera

MD-500Ap

HDTV 1080p/720p • 5M/4M/3M/2M/1.3M Resolution Supported



- Most Intelligent and Professional 5M Outdoor Mini Dome Camera
- HDTV Quality (Full HD 1080p @ 30fps Streaming)
- Wide Camera Angle Adjustment with Pan 35°, Tilt 0-90°, Rotation 180°
- **Intelligent Multi-Profile Sensor Management[®]** for Different Environments
- Weather-proof (IP67) and Vandal-proof (IK10) with Stylish Design
- Wide Angle of View and Easy to Adjust Focus
- EN50155 Certify with Anti Vibration and Shock
- Built-In Micro SD slot/ TV out Connector Supported
- PoE(802.3af) / M12 Connector / DC12V Supported






Photo Indication & Dimension Diagram



- 1 Microphone Hole
 - 2 Security Screws
 - 3 Screw Hole
 - 4 PAL/ NTSC Switch
 - 5 TV out Connector
 - 6 LED Indicators
 - 7 Reset Button Slot
 - 8 Micro SD/SDHC Card
 - 9 RJ45 Connector (for Ethernet and PoE:802.3.af)
 - 10 M12 Connector(*)
 - 11 DC12V Connector (*)
- *Cable Connector Variants***



Camera

Hardware System	CPU: 533 MHz Flash: 32M RAM: 256M DDR
Image Sensor	Sensor Type : 1/2.5" CMOS Sensor Sensor Resolution : 2592 x 1944 pixel
Camera Angle Adjustment	Pan ± 35° / Tilt 0-90° / Rotation ± 180°
Minimum Illumination	1 lux (F1.6 , 1/5s , BW) 2Lux (F1.6 , 1/5s , Color)
Local Storage	Built-in Micro SD/SDHC Memory Card Slot


Video

Compression Streaming	H.264 / MPEG4 / MJPEG Simultaneous multiple streams
Video Setting	Multi-Profile Image Management: Day/ Night/ Sunset/ User 1/ User 2 Auto Exposure/ Gain/ White Balance Control Manual Exposure Control: 1/20000~1/5s Manual Gain Control: 1X ~ 32X Manual White Balance Control:2000K~7000K
S/N Ratio	38.1dB
Image Resolution	5M : 2592x1944 @ 10fps (5M supports MJPEG only) 4M : 2304x1728 @ 15fps 3M : 2048x1536 @ 18fps 2M (Full HD) : 1920x1080 @ 30fps 1M (HDTV) : 1280x720 @ 30fps

Events and Alarm Management

Events	Motion Detection Schedule Audio Detection
Alarm	Stream/Snapshot to FTP/Email/Samba/SD-Card HTTP/Email Notification

Product Distinction



Audio

Audio Streaming	1-way Audio Support
Audio Compression	G.711, AMR (8 kHz, Mono, PCM)

Audio Input/ Output	Built-in MIC
----------------------------	--------------

General

Communication	Ethernet : one 10/100Mbps RJ-45 Supported Protocols : TCP/IP, UDP, ICMP, DHCP, NTP, DNS, DDNS, SMTP, FTP, HTTP, Samba, PPPoE, UPnP, RTP, RTSP, RTCP, IPv6
----------------------	--

Connectors	Cables with different Options A. RJ45,DC12V B. M12
-------------------	--

Power Input	PoE 802.3af/ M12/ DC12V
--------------------	-------------------------

Max. Power Consumption	5.5 watts
-------------------------------	-----------

Environment	Operating Temperature -20°C ~ 50°C (-4°F ~122°F), Operating Humidity : 10% ~ 80%
--------------------	---

Dimension	110(L) X110(W) X 53.7(H) mm
------------------	-----------------------------

Weight	460g/1.02lb
---------------	-------------

Housing	Weather-proof (IP67) Vandal-proof (IK10)
----------------	---

Certification	FCC, CE, EN50155, IK10
----------------------	------------------------

Viewing System Requirements	OS: Microsoft Windows 7/Vista/XP/2000 Browser: Mozilla Firefox, Internet Explorer 6/7 or above, Safari, Google Chrome Cell Phone: 3GPP player Real Player: 10.5 or above Quick Time: 6.6 or above VLC
------------------------------------	--

Warranty	Limited 2-year warranty
-----------------	-------------------------

Lens Spec				
MD-500Ap	f=3.6mm	f=4mm	f=6mm	f=8mm
Lens Type	Board Lens	Board Lens	Board Lens	Board Lens
F Number	F=1.6	F=1.6	F=1.6	F=1.6
FOV(H/V/D)	92°/68°/115°	90°/67°/112°	55°/40°/70°	41°/30°/52

Work Best With

Camera Accessories Options



M12 mount Lens



BNCMD-01
TV out Connector Line

Network Equipment Options



PS-588I
8-port 10/100M PoE Fast Ethernet Switch



PS-7242IL-AF
24-port 10/100M PoE Web Smart Ethernet Switch