


NSM5300 Series Network Storage Manager

400 MBPS RECORDING THROUGHPUT, UP TO 72 TB OF RAW CAPACITY, RAID 6

Product Features

- Recording Throughput up to 400 Mbps Meets Demanding Performance Requirements for Write-Intensive Applications
- Hardware Designed to Eliminate Single Points of Failure, Including Redundant Fans, Power Supplies, and RAID 6 Storage for Optimum Reliability
- Pooled Storage Management Provides Automatic Distributed Load Balancing and Active-Active Failover Within a Storage Pool to Ensure Continued Recording if Catastrophic Failure Occurs
- Hot Standby Failover Provides Redundancy in Installations Where Storage Pooling Cannot Be Utilized.
- Multicast Recording Support Allows for Recording of Multicast Data Streams for Restricted Bandwidth Scenarios
- Redundant Recording Ensures Duplication of Vital Data for Mission-Critical Applications



- Built-in EnduraStor™ Storage Management Increases Storage Efficiency by Pruning Recorded Streams Based on Age and Priority
- Ability to Serve 32 Simultaneous Playback Streams Per Storage Pool
- Performance Levels Maintained in Normal and RAID Error Conditions
- Built-in Diagnostic Monitoring Provides Preventative Maintenance and SNMP Monitoring
- Reduced Cost of Ownership and Increased Energy Efficiency Through Consolidation of Multiple Hardware Components into a Fully Integrated Chassis
- VideoXpert Ready. Migrate to VideoXpert, bringing your products forward into a next generation VMS

The NSM5300 Series delivers industry leading performance and innovation for mission-critical storage needs. The combination of high performance, scalable hardware design and advanced software capabilities enables the NSM5300 to meet the unique storage needs of physical security and surveillance applications.

Hardware Built for Performance, Reliability, and Scalability

The demands of surveillance applications place unique strains on storage subsystems. Storage systems require the bandwidth and capacity to keep up with incoming streams. They must also simultaneously manage all other common disk and RAID functions. In addition, physical security applications are almost always mission critical. Any downtime, degraded performance for routine maintenance, or loss of recorded footage is extremely disruptive to the organization's physical security mission.

The NSM5300 has been engineered to meet these unique performance and reliability demands. Custom hardware components, to eliminate common performance choke points to a patented scheme for writing content to a disk drive, have been specifically designed to deliver sustained high throughput for recording and playback. The NSM5300 is capable of a maximum of 400 Mbps of throughput for incoming streams while delivering 32 simultaneous playback streams per storage pool. This performance is maintained whether the system is operating under normal conditions, dealing with disk drive errors, or rebuilding the RAID array.

The NSM5300 improves the total cost of ownership and energy efficiency by consolidating disparate components into a single chassis. The 400 Mbps throughput provides double the improvement over Pelco's first generation integrated recorder, allowing users to service far more data streams in one storage unit than previously possible. In addition, with the integration of the storage controller functionality into the storage chassis, cost and energy efficiency is optimized by eliminating the cost of additional servers and the associated heating, ventilation, and cooling costs. Finally, the use of lower power components and adaptive cooling inside the chassis manage power dissipation based on load requirements.

Reliability is enhanced through the use of redundancy at all common failure points. A USB Flash drive is used to host the operating system for higher reliability than traditional hard disk drives. To mitigate any downtime resulting from USB Flash drive errors, the database is striped across the storage array. The RAID 6 storage configuration provides double parity protection of recorded data. The hard drive bay is cooled through the use of high capacity, redundant fans to ensure that the drives are kept at an optimum operating temperature. Finally, fully redundant power supplies guard against any power supply failure.

This Endura distributed, network-based product is available only to certified dealers/integrators. Please contact your local sales representative for details on certification applications and requirements. Additional information on Endura products and certifications may be found at <http://www.pelco.com/endura>.



by Schneider Electric

International Standards
Organization Registered Firm;
ISO 9001 Quality System



C4051 / REVISED 1-3-18

TECHNICAL SPECIFICATIONS

As with any system, maintenance is an important and vital part of sustained operation. The NSM5300 incorporates various innovations to make maintenance more efficient and to allow the system to continue operating at peak performance levels. Temperature sensors throughout the chassis detect possible air-flow obstruction or clogged intake filters. The use of enterprise-class SAS® technology provides advanced enclosure management and monitoring. Notifications of potential or actual issues are transmitted to the specified user interfaces for action.

Software Built for Flexibility, Reliability, Cost Optimization

In addition to unique strains placed on hardware components, surveillance applications also demand innovations in software. Recording software must accommodate automatic failover should a catastrophic failure occur. Recording software must deal with file fragmentation caused by overwrite, locking of video clips, and managing metadata associated with alarms and events. Finally, recording software must deal with the escalating cost of storage by finding innovative ways to manage recorded content. This ensures that the user extracts the most value from the cost of the storage subsystem.

The NSM5300 supports the pooling of multiple recorders to provide for automatic retention balancing and failover. Up to six NSM5300 nodes can be placed into the same storage pool. One of the NSM5300s in the pool acts as the master and manages the assignment of incoming streams, health monitoring, and redistribution of the recording load. Should a unit fail, the given streams are automatically redistributed to the remaining units in the storage pool. When the failed unit is brought back on line, the recording load is redistributed to balance the video retention period across the recording pool. This capability also allows users to dynamically add additional storage to a pool as their retention needs change. Single NSM5300s can be monitored by another NSM5300 or an entire storage pool when the single NSM5300 cannot be incorporated into a standard storage pool.

For mission-critical applications where business continuity is essential, the NSM5300 supports redundant recording. Independent schedules can be created on both the primary and redundant storage pools to ensure that the most vital data is duplicated across physical boundaries.

The NSM5300 incorporates an improved version of Pelco's patented EnduraStor™ storage optimization technology. EnduraStor was developed to manage the cost of storing high resolution, high-frame rate video by leveraging the fact that the value of recorded video is typically higher immediately following an incident. Organizations are capable of specifying a desired delay period during which all recorded video will be kept at 30 images per second (25 ips for PAL). As the age of video available on hard disk drives exceeds the delay period, it is automatically pruned to a lower frame rate, thus freeing up storage capacity for new data. The NSM5300 incorporates advancements in the EnduraStor algorithm, which gives administrators the option of classifying the priority level of alarm or event video to retain the full frame rate.

The NSM5300 is built upon the proven stability and robustness of its Linux®-based operating system. It utilizes an XFS file system and automated defragmentation routines to keep the database from becoming fragmented. XFS has been proven to be a superior file format for the rigors of surveillance recording applications than an NTFS file system, which is standard with Windows®-based recorders.

The NSM5300 incorporates a number of diagnostic monitoring functions that serve vital roles in notifying operators of potential problems and failures. Integrated diagnostics utilize on-board LED indicators to display warnings and failures on the NSM5300 and then it reports these failures to operators. The NSM5300 monitors and provides warning messages for items such as retention time issues, accumulation of software errors, network errors that result in packet loss, and changes to network link speeds. It also monitors and reports hardware diagnostics such as temperatures approaching established thresholds, hard disk drive failures, fan failures, power supply failures, or when a stream or a NSM5300 is off line. Finally, the NSM5300 can communicate to an APC Smart-UPS® series uninterruptible power supply to provide battery status information and initiate a graceful shutdown if the available charge falls below its designated threshold.

TECHNICAL SPECIFICATIONS

MODELS

The following table describes the NSM5300 model numbers.

Model	Storage
NSM5300 (no expansion)	24 TB
	48 TB
	72 TB

SUPPLIED ACCESSORIES

Power Cord	3 power cords (US, EU, and United Kingdom)
Rack Mount Kit	Brackets, rails, and hardware

OPTIONAL POWER ACCESSORIES

PWRCRD-S-AR	Standard power cord, Argentina
PWRCRD-S-AU	Standard power cord, Australia
PWRCRD-S-EU	Standard power cord, Europe
PWRCRD-S-UK	Standard power cord, United Kingdom
PWRCRD-S-US	Standard power cord, United States
PWRCRD-R-AR	Round power cord, Argentina
PWRCRD-R-AU	Round power cord, Australia
PWRCRD-R-EU	Round power cord, Europe
PWRCRD-R-UK	Round power cord, United Kingdom
PWRCRD-R-US	Round power cord, United States

SYSTEM

Operating System	Linux
RAID Level	RAID 6
Effective Capacity	
NSM5300-24	18.166 TB
NSM5300-48	36.356 TB
NSM5300-72	54.549 TB
Drive Interface	SAS/SATA II

Recommended PC Requirements

Web Browser	Microsoft® Internet Explorer® 6.x (or later) with Adobe® Flash® Player 10 (or later)
-------------	--

NETWORK

Interface	2, 1 Gbps Ethernet RJ-45 ports (1000Base-T)
Auxiliary Interfaces	
USB 2.0	3 ports (1 front, 2 rear)
VGA	2 ports (1 front, 1 rear)

POWER

Power Input	100 to 240 VAC, 50/60 Hz, autoranging
Power Supply	Internal, dual-redundant, hot swappable

ENVIRONMENTAL

Operating Temperature	10° to 35°C (50° to 95°F) at unit air intake
Storage Temperature	-40° to 65°C (-40° to 149°F)
Operating Humidity	10% to 80% relative humidity
Maximum Altitude	

Operating	3,048 m (10,000 ft)
Storage	12,000 m (39,370 ft)
Maximum Vibration	
Operating	0.26 Grms at 5 Hz to 350 Hz (all operation orientations)
Storage	1.88 Grms at 10 Hz to 500 Hz for 15 min (all six sides tested)

Note: The temperature at the unit air intake, measured at the front of the bezel, can be significantly higher than room temperature. Temperature is affected by rack configuration, floor layout, air conditioning strategy, and other issues. To prevent hard disk drive failure and unit damage, make sure the temperature at the air intake of the unit is continuously within the operating temperature range.

PHYSICAL

Construction	Steel cabinet
Finish	
Front Panel	Gray metallic
Chassis	Steel finish
Dimensions (without rails)	75.5 x 48.3 x 8.8 cm (29.8" D x 19.0" W x 3.5" H)
Unit Weight	
Empty (without drives)	10.3 kg (22.7 lb)
Loaded (with drives)	32.5 kg (71.5 lb)
Mounting Options	Rack, 2 RU per unit (rack rails and hardware are supplied)

CERTIFICATIONS/RATINGS

- CE, Class A
- FCC, Class A
- UL/cUL Listed
- RCM
- CCC
- KC
- NOM

Pelco by Schneider Electric

625 W. Alluvial, Fresno, California 93711 United States
USA & Canada Tel (800) 289-9100 Fax (800) 289-9150
International Tel +1 (559) 292-1981 Fax +1 (559) 348-1120
www.pelco.com **www.pelco.com/community**

Pelco, the Pelco logo, and other trademarks associated with Pelco products referred to in this publication are trademarks of Pelco, Inc. or its affiliates. ONVIF and the ONVIF logo are trademarks of ONVIF Inc. All other product names and services are the property of their respective companies. Product specifications and availability are subject to change without notice. ©Copyright 2017 Pelco, Inc. All rights reserved.