



The NetWave® industrially hardened wireless Ethernet transmission link can be configured through the embedded User Interface as a Client or as an Access Point. This point-to-multipoint model allows multiple Ethernet endpoints to be connected to a central Access Point. Up to 15 endpoints can be linked to a central access point. The NW1/M and NW2/M support up to 95Mbps throughput using MIMO technology. The units can be powered by an IEEE 802.3af PoE compliant device or through the supplied power injection module. The NW1/M is FCC certified for use in North America and the NW2/M is ETSI, DFS and TPC certified for use in the European Union. The NW(1,2)/M is an ultra-small form factor addition to the ComNet NetWave product family.

FEATURES

- › Lifetime Warranty
- › Up to 95Mbps Throughput
- › 802.11a/n Compliant
- › Distances up to 2 mi (FCC) or 2km (ETSI)
- › Powered by the included power injection module or by an IEEE802.3af PoE compliant device
- › Environmentally Hardened -40° to +75°C
- › Meets class IP67 dust and water immersion protection standards
- › ETSI Standards (EU Region only):
 - DFS Dynamic Frequency Selection
 - TPC Transmit Power Control
- › Secure transmission: WPA2 - AES or TKIP encryption
- › ComNet Antenna alignment feature eases installation and setup
- › RF Spectrum Survey Tools
- › Antenna Alignment Tools
- › LED array displays unit operational status along with received signal strength
- › Optional Antenna Configurations Available

APPLICATIONS

- › Point to Multi-Point topologies whereby several Clients connect to one Access Point
- › Simple to deploy and cost-effective alternative to physical connections to Ethernet edge equipment
- › Integration of Ethernet where right-of-way issues mandate wireless communications
- › ITS traffic signalization networks and Video Detection Systems (VDS)
- › ITS roadside and city center CCTV surveillance, and surveillance of high-value or mission-critical assets
- › Wireless communications in manufacturing, petrochemical refineries, wastewater treatment facilities, and other industrial automation and control applications operating in harsh or out-of-plant environments
- › Electrical substation video and perimeter surveillance

SPECIFICATIONS

Wireless Radio

EIRP	NW1/M (FCC): Up to +36dBm for point to multipoint deployments, +42dBm for point to point deployments with MAC-lock feature enabled NW2/M (ETSI): +30dBm
RF Output	+26dBm Rated Transmitter
Operational Frequency	5180GHz - 5825GHz, Region-dependent. Not all frequencies are supported in all regions. Contact ComNet for frequencies supported in your region.
Bandwidths	20 and 40MHz

Standard Internal Antenna

Antenna	Internal 16dBi Dual Polarized Directional
Gain	16dBi
Azimuth	30° Horizontal/Vertical
Elevation	30° Horizontal/Vertical

IA870 Optional Internal Antenna

Antenna	Internal 8dBi Dual Polarized Directional
Gain	8dBi
Azimuth	70° Horizontal/Vertical
Elevation	30° Horizontal/Vertical

Connectors

10/100 Ethernet	RJ-45, Sealed Cable Gland
-----------------	---------------------------

Indicating LEDs

Power On, Ethernet Link, Signal Strength

Software Features

Addressing	Static IP / DHCP Client / DHCP Server
SNMP	V3
Telnet Server	Syslog
Dynamic DNS	802.1q VLAN support
Embedded Firewall	QoS support
Ability to Assign Static Routes	NTP Client
Spanning Tree Protocol support	
802.1x Port-Based Network Access Control	
User-Configurable Watchdog and Auto-Reboot Mechanism	
Multi-Level Configuration and Monitoring Login Accounts	
User Configurable Long Range Parameters	

Power

Operating Voltage	42 to 57 VDC
Power Consumption	5.5 W Max
PD Power	IEEE802.3af PD compliant

Mechanical

Size (L x W x H)	7.4 x 7.4 x 2.2 in (18.5 x 18.5 x 5.6 cm)
Shipping Weight:	<2lbs/0.9kg

Environmental

MTBF	>100,000 hours
Operating Temp	-40° C to +75° C
Storage Temp	-40° C to +85° C
Relative Humidity	5% to 95%

NOTE: In a continuing effort to improve and advance technology, product specifications are subject to change without notice.

ORDERING INFORMATION

Part Number	Description
NW1/M	Industrially Hardened Mini Point-to-Multipoint Wireless Ethernet Unit, Supports distances up to 2 mi/3.2 km, FCC certified for North America
NW2/M	Industrially Hardened Mini Point-to-Multipoint Wireless Ethernet Unit, Supports distances up to 2 km/1.25 mi, ETSI certified for European Union
Included Accessories	Power Kit with Power Supply and Passive Power Injector Pole Mounting Hardware Kit
Options	Add /IA870 for 8dBi/70° beamwidth internal antenna option (Recommended for multipoint Access Points. Extra charge, consult factory.) Add '/C' for Conformally Coated Circuit Boards (Extra charge, consult factory)



AGENCY COMPLIANCE



 Low Power Consumption

TYPICAL APPLICATION

Point-to-Multipoint Topology



LEGEND

- WIRELESS
- CAT5
- POWER
- ETHERNET DATA

Point-to-Point Topology Utilizing Dual Ports

