

4MP 30X PTZ IP Camera with Wall Mount Bracket

O4P30X 4.5-135mm 30x optical zoom lens, white housing

Features

- Supports up to 4MP @ 30fps in 16:9 widescreen format
- 30x optical zoom
- Built-in PoE+ (IEEE 802.3at)
- True WDR (wide dynamic range) operation
- 2-way audio communication
- Micro SD card slot for edge recording (card not included)
- Sensor inputs and relay outputs
- RS485 control
- 24VAC operation
- IP66 compliant, weather resistant
- IK10 complaint, vandal resistant
- Wall mount bracket included
- Conformant with ONVIF Profile S
- 1 year warranty



Camera Specifications

Image Sensor Progressive scan 1/3" CMOS, 4MP
 Maximum Resolution 2592 x 1520
 Minimum Illumination F1.6, 0.05 lux color; 0.005 lux BW
 White Balance Auto / Manual
 Compensation WDR (120dB) / BLC / HLC
 Day/Night IR cut filter
 DNR 2D/3D

Video Specifications

Supported Resolutions 2592x1520 / 1920 x 1080 / 1280x720 @ 30fps
 Compression H.264, MJPEG
 Bitrate Control VBR, CBR
 Multiple Streaming 3 streams

Audio Specifications

Mono Input G.711
 Mono Output G.711

PTZ Specifications

Pan Range 0°-360° endless
 Tilt Range 0° - 180° (auto flip)
 Manual Speed Pan: 300°/sec; Tilt: 150°/sec
 Preset Speed Pan: 600°/sec; Tilt: 500°/sec
 Presets 300 positions
 Tour Max. 8 programmable group tours
 Pattern 5 programmable patterns

External Terminal Specifications

Ethernet 10/100 Mbps
 Audio 1 input, 1 output
 Video BNC analog output
 Alarm 7 sensor inputs, 2 relay outputs
 Control RS485
 Storage Micro SD slot (128GB max)

Network Specifications

Protocols IPv4, IPv6, TCP, UDP, RTCP, RTP, RTSP, HTTP, HTTPS, SMTP, SNMP, UPnP, FTP, DHCP, Bonjour, QoS, 802.1x

Network Specifications (continued)

DDNS support Speco DDNS (free of charge)
 Security User ID & Password protection, IP address filtering
 User Access 20 simultaneous users (performance may vary depending on resolution and number of connections)

System Specifications

PoE PoE+ (IEEE 802.3at)
 Analytics Motion detection, audio detection, face detection
 Alarm Triggers Analytics, network loss
 Alarm Events FTP video/image file upload, email image upload, micro SD card recording, relay out
 Video Buffer Configurable pre-record & post-record
 Image Settings Privacy mask

Client Specifications

Web Browser Support Windows (Internet Explorer 11)
 PC Application SecureGuard®
 Mobile Application SecureGuard® Mobile (iPhone® & Android™)

Operating & Unit Specifications

Power PoE, 24VAC (power supply not included)
 Power Consumption 22W max
 Operating Temperature -40°F - 158°F
 Operating Humidity 0% - 95% RH
 Unit Dimensions 8.7" (Dia.) x 11.7" (H)
 Unit Weight 13.7 lbs.
 Certifications FCC, RoHS, UL

Optional Accessories

