

2 MEGAPIXEL | 1080p

# PAR-C2TXIR2812

2 Megapixel/1080p TVI Turret, 2.8-12mm, 65' EXIR Range, TVI/AHD/Analog Output, 12VDC



## Features

- 2 Megapixel 1080p Resolution
- TVI & AHD/Analog Outputs
- Varifocal 2.8-12mm Lens
- True Day/Night
- Digital Wide Dynamic Range
- EXIR Technology up to 98' IR Range
- UTC Function
- IP66 Weather Resistant
- 12VDC Operation

1080p	TVI, AHD/CVBS	2.8-12mm
True Day/Night	D-WDR	IR 98' Range
UTC Up The Cable Control	IP66 Weather Resistant	IK10 Vandal Resistant
DC12V		

Image Sensor	1/3" CMOS
Resolution	1920 x 1080
Image System	NTSC/PAL
Auto Iris	Fixed Iris
Min Illumination	0 Lux (IR On)
Lens	2.8-12mm
Lens Mount	D14
IR Distance	98'
Environmental	IP66 Weather Resistant
Video Output	TVI & AHD / CVBS Selectable
Image Size	1080p (1920 x 1080)
Frame Rate	30 FPS (60Hz), 25 FPS (50Hz)
Angle Adjustment	3-Axis
Screen Display	2 Languages Supported (English & Chinese)
Function Control	OSD/UTC
Day & Night	Yes (ICR)
BLC & HLC	Yes
WDR	Digital WDR
Digital NR	Yes
Defect Correction	Live Defective Pixel Correction
S/N Ratio	>52dB (AGC Off)
Electronic Shutter	1/60s ~ 1/100000s (NTSC), 1/50s ~ 1/100000s (PAL)
AGC	Yes
White Balance	ATW, AWC-SET, Manual
Advanced Image	Adjustable Sharpness, Saturation, Brightness
Power Supply	DC12V (+ 10%)
Working Environment	-4° ~ 122° F (-20° ~ 50° C) 10%~90% Humidity
Dimensions	Ø 4.29 x 5.11" (Ø 109 x 130mm)

## Ordering Information

PAR-C2TXIR2812: 1080p Turret, 2.8-12mm

PARAMOUNT 