

QER Series

19" Knock-Down Equipment Racks

Features

- Available in 6 panel heights, 2 rack depths (20" and 26") and a very narrow 20" rack width.
- Easy to assemble (less than 3 minutes).
- Squaring brackets allow you to assemble the frame with just eight bolts.
- Available in Preconfigured Kits (including drawers, shelves, casters, hardware, power strips).
- EIA/TIA compliant
- 10 year warranty

Options

- Doors (face mount, curved and flat) available as solid, vented and polycarbonate.
- Side panels (removable) are 20-gauge steel and come with keyed lock.
- Rear panel is 20-gauge steel and come with ¼ turn lock.
- Adjustable split rails are 11-gauge steel for rear equipment support.
- Available accessories: drawers, shelves, lacing bars, adjustable lacing bars, power strip (vertical and horizontal, hardware kit, cable raceway, joining kit, front trim kit (curved and flat), blanking panels (solid and vented), CD and DVD holder,
- Available cooling accessories: Fan panels (plain and with display) and fan stacks (all available with ultra quiet fans).



QER Specification

Product Type	Part Number Chart	Specification
Floor Standing Racks and Enclosures	Q-43-20 Q-43-26 Q-37-20 Q-37-26 Q-29-20 Q-29-26 Q-21-20 Q-21-26 Q-14-20 Q-14-26 Q-8-20 Q-8-26	Peerless-AV model number Q-xx-xx (refer to part number chart for specific part number) is an EIA compliant 19" (482.6mm) floor standing/gang-able rack. Overall dimensions of rack shall be ___"H x 20"W x ___"D (refer to drawing chart). Useable height shall be ___ rack units, useable depth shall be ___" (refer to drawing chart). This rack features a multi-formed construction that provides a static load capacity of UL listed 600 lbs (272 kg). Rack shall have knock-down construction and ready to assemble. Rack shall be constructed of the following components: top shall be 14-gauge (1.9mm) steel, skirted/integrated caster base 14-gauge (1.9mm) steel, main rails 11-gauge (3mm) steel with tapped 10-32 mounting holes in universal EIA spacing, self locking and self squaring, black powder-coat finish and numbered rack units, cross channel shall tool-less 14-gauge (1.9mm) steel. All structural elements shall be pre-treated w/ iron phosphate (5 stages wash) and finished in a black powder coat. Rack main rails shall lock firmly in place and secured with 1 screw per corner. Mounting features both front and back to accept optional fully reversible face mount door. Under normal use and conditions, Peerless-AV warranties the SR rack to be free from defects in material or workmanship, under normal use (original owner) for ten years.