

Wireless Backup Camera System with Dual Screen Monitor

RVS - 2CAM

REAR VIEW
SAFETY
A Safe Fleet Brand



Our Wireless Camera System with Dual Screen Display comes with a digital wireless connection and a split screen monitor to view two cameras at the same time. With this new wireless technology, we guarantee no interference for up to 70ft! The monitor is a 7" TFT LCD color display, comes with distance grid lines and has the ability to view one camera full screen or two with a split screen. The wireless backup camera is completely waterproof, boasts a 130° viewing angle, a Sharp® CCD High Definition lens and 9 infra-red night vision lights which enable you to see in total darkness. The Auto Pair function lets you pair the system without leaving your cab, making this camera system perfect for truck and trailer applications.

Wireless Backup Camera System, Dual Screen Monitor with Cigarette Lighter Adaptor

RVS - 2CAM

REAR VIEW SAFETY

A Safe Fleet Brand

- 7" DIGITAL TFT LCD Color monitor with mirror image capability
- 1/4 Sharp® color CCD, 250k pixels, 2.1 mm wide lens with 130° angle
- Shock resistant with a 20G Vibration and 100G impact rating
- Digital wireless connectivity between devices



MONITOR

MONITOR TYPE	TFT LCD
SCREEN SIZE	7"
DOT RESOLUTION	800 X 3 (RGB) X 480
DISPLAY FORMAT/CONTRAST	16:9 / 500:1
DISPLAY BRIGHTNESS	400CD/m ²
VIEWING ANGLE	U:50° D:60° L/R:70°
VIDEO INPUT	2 CHANNEL
VIDEO SOURCE	1VP-P, 75Ω
POWER SUPPLY	DC 12V-24V (+/- 10%)
POWER CONSUMPTION	5W
OPERATING TEMPERATURE	-30°C ~ +80° C
VIDEO SYSTEM	AUTO NTSC/PAL
OVERALL DIMENSIONS	7" (L) X 5" (H) X 1" (D)
WEIGHT	400G
VIBRATION RATING	5G
DOT PITCH	0.192 (H) X 0.1805 (V)
SYNC SYSTEM	INTERNAL

CAMERA

CAMERA TYPE	1/4" SHARP® COLOR CCD
PICTURE ELEMENTS	250,000 PIXELS
GAMMA CORRECTION	R=0.45 TO 1.0
VIEWING ANGLE	130°
IMAGE SENSOR	540 TV LINES PAL: 752 (H) X 582 (V) NTSC: 769 (H) X 494 (V)
LENS	2.1MM
WATERPROOF RATING	IP68
VIEW ANGLE	130°
SYNC SYSTEM	INTERNAL SYNCHRONIZATION
INFRA- RED DISTANCE	50 FEET (9 INFRARED)
USABLE ILLUMINATION	0 LUX (IR ON)
POWER SOURCE	DC 12V/3A (+/- 10%)
S/N RATIO	MORE THAN 48DB
ELECTRONIC IRIS	1/50, 160-1/100,000SEC
VIDEO OUTPUT	1VP.P 75OHM
IR SWITCH CONTROL	ACDS AUTOMATIC CONTROL
VIBRATION AND SHOCK RATING	20G / 100G