

BACKUP CAMERA SYSTEM WITH HEATED CAMERA



RVS-812613-NM



This heated rear view camera system is complete with a crystal clear 7" LED DIGITAL Display color monitor with mirror image capability and distance grid lines and one (1) rear view back up camera with 120° viewing angle and built in heater to withstand the coldest weather. The backup camera's night vision boasts a 50 foot range with 30 built in Infra-reds so you can see in total darkness. The system includes all the wires, connectors and mounts you will need. The backup camera is completely weatherproof, with an IP69K rating to withstand power washing, strong and reliable, shock resistant and has a 10G vibration rating. It comes with a full year warranty.

NOTE: MINOR DETAILS MAY CHANGE BASED ON ITEM CONFIGURATION

BACKUP CAMERA SYSTEM WITH HEATED CAMERA

RVS

A Safe Fleet Brand

- 7" LED DIGITAL PANEL 16:09 WIDE SCREEN
- 2.1 MM WIDE LENS WITH 120° ANGLE
- 50 FOOT INFRA-RED NIGHT VISION
- SHOCK RESISTANT WITH A 10G VIBRATION RATING
- IP69K WEATHERPROOF - CAN WITHSTAND ALL WEATHER CONDITIONS



MONITOR

TYPE	LED DIGITAL PANEL
SCREEN SIZE	7"
DOT RESOLUTION	800 X 3 (RGB) X 480
DISPLAY FORMAT/CONTRAST	16:09 / 500:01:00
DISPLAY BRIGHTNESS	400CD/m ²
VIEWING ANGLE	U:50° D:60° L/R:70°
VIDEO INPUT	3 CHANNEL CVBS
VIDEO SOURCE	1VP - P, 75Ω
POWER SUPPLY	DC 9V-32V
POWER CONSUMPTION	5W
AUDIO OUTPUT	0.5W SPEAKER
OPERATING TEMPERATURE	-20°C ~ +70°C
STORAGE TEMPERATURE	-30°C ~ +85°C
VIDEO SYSTEM	AUTO NTSC/PAL
OVERALL DIMENSIONS	7" (L) X 5" (H) X 1" (D)
WEIGHT	400G
IMPACT RATING	5G
DOT PITCH	0.1926 (H) X 0.1710 (V)
ACTIVE AREA	154.08(H) X 85.92(V) MM
SYNC SYSTEM	INTERNAL

NOTE: MINOR DETAILS MAY CHANGE BASED ON ITEM CONFIGURATION

CAMERA

IMAGE DEVICE	1/3" SONY® SUPER HAD CCD
TV SYSTEM	PAL / NTSC
TOTAL NUMBER OF PIXELS	PAL: 537 (H) × 597 (V) / NTSC: 537 (H) × 505 (V)
EFFECTIVE PIXELS	PAL: 500 (H) × 582 (V) / NTSC: 510 (H) × 492 (V)
SENSING AREA	4.9 MM (H) × 3.7 MM (V)
SYNC. SYSTEM	INTERNAL
RESOLUTION	700 TV LINES
MINIMUM ILLUMINATION	0 LUX (WITH IR)
MICROPHONE	YES
VIDEO OUTPUT	COMPOSITE SIGNAL (1.0 VP - P, 75 Ω)
GAMMA CORRECTION	0.45
AGC	ON
S/N RATIO	BETTER THAN 48 DB
WHITE BALANCE	AUTO
ELECTRONIC SHUTTER	1/50-1/100,000 SEC. / 1/60-1/100,000 SEC.
BLC	AUTO
CURRENT CONSUMPTION	MAX. 300 MA
POWER SUPPLY	DC 9V-32V
ANTI-VIBRATION	5.9 G
OPERATING TEMPERATURE	-45°C~70°C, RH 95% MAX.
STORAGE TEMPERATURE	-45°C~80°C, RH 95% MAX.
LENS	3.6 MM OPTIONAL
LENS ANGLE	120°