

SMI-3 2 Channel Audio Surveillance kit

Sound Surveillance tm

Description

2 zone audio surveillance kit designed to connect to audio recorders, CCTV monitors (with built in speakers), video recorders, DVRs, remote monitoring equipment, etc.



Includes

- 2 SM1 Pre-amplified microphones
- SMI-2 Interface adapter.
- SM1 mounting screws
- 12 VDC AC adapter.
- 2 3' RCA or 3.5mm Patch cables.
- 2 ETS warning labels
- Installation Instructions.

Options

- SPECIFY: RCA output connectors OR 3.5mm when ordering.

Wiring Requirements

- Stranded 22-gauge, 2-conductor shielded cable w/drain wire.
Max. cable length per mic. 1500'

SM1 Microphone Specifications

- Omni-directional Electret element.
25' range in all directions.
- Frequency response: 200-16Khz.
- Low noise MOSFET pre-amplifier.
- Line level, unbalanced output.
- Adjustable gain.
- Treble boost circuit. Selectable on/off.
Enhances clarity of time lapse recordings.
- Limiter circuit. Selectable on/off.
- 3 position Euro-style connector makes cable termination fast and clean.
- Flush mountable. Can be mounted on a single gang electrical box.
- Power: 12 VDC @ 10mA
- See SM1 data sheet for more information.

SMI-2 Interface Adapter Specifications

- RCA or 3.5mm jacks for connection to DVRs, Remote monitoring equipment, etc.
- Euro-style connectors makes cable terminations fast and clean.
- LED power indicator.
- Power: 12 VDC @ 20mA
- Reverse polarity protected and fused.
- Dimensions: L 3.3 x W 2.0 x H 1.6
- See SMI-2 data sheet for more information.