


## Intensifier H® Indoor/Outdoor Miniature Dome Camera

**HINTMD1H** 3.6mm fixed lens, dark grey housing

### Features

- 700 TV lines of resolution
- Amplify existing light with no distance limitations
- See color at night or in low light
- No problems caused by objects that reflect or absorb IR light sources
- Minimum illumination 0.00002 lux (Intensify @ 512x)
- Presets for different lighting scenarios
- 3-axis design, both wall and ceiling mountable
- Digital wide dynamic range
- Full OSD operation
- IP66 compliant
- 12VDC/24VAC dual voltage operation
- 5 year warranty



### Specifications

Image Sensor..... 1/3" color 960H CCD

Resolution ..... 700 TV lines

Minimum Illumination ..... CDS Off: 0.15 lux  
CDS On: 0.00002 lux

S/N Ratio..... 52dB

Effective Pixels ..... 976 (H) x 494 (V)

Total Pixels ..... 1020 (H) x 508 (V)

Shutter..... 1/60 sec – 1/120,000 sec

OSD..... Yes

Synchronization..... Internal

Privacy..... On / Off (8 zones)

Motion Detection ..... On / Off (4 zones)

Mirror ..... On / Off

DNR..... High / Middle / Low / Off

White Balance ..... ATW / Push / Manual

Image ..... BLC / HLC / D-WDR / Defog

AGC..... Level adjustable (0-20)

TV System..... NTSC

Operating Temperature ..... -4° F – 122° F

Operating Humidity ..... 20% – 80% RH

Power Supply ..... 12VDC, 24VAC

(power supply not included)

Power Consumption..... 2.2W max

Dimensions ..... 4.8" (Dia.) x 2.17" (H)

Weight ..... 12 oz.

### Optional Accessories



**INTPM\***  
Pendant  
Mount

\* use with OADP4



**CVCJBD\***  
Dome Camera  
Junction Box



**INTCM**  
Corner/Pole  
Adaptor  
(use with  
INTWM only)



**INTWM\***  
Wall Mount



**OADP4**  
Adaptor Plate



**PSW4**  
24VAC  
Power Supply



**PSW5**  
12VDC  
Power Supply